



Declaration of Performance nr.: V1 (EN)

1. Product type	Shuttering block
2. Identification	Concrete shuttering block
3. Intended use(s)	External walls and partitions. Intended to be laid dry, or with mortar, and then filled with concrete or mortar. Non-load bearing blocks.
4. Manufacturer's name and contact address	A/S Ikast Betonvarefabrik Lysholt allé 4 DK-7430 Ikast +45 97 15 20 22 www.ibf.dk
5. Name and contact address of the authorised representative	Not relevant
6. System or systems of assessment and verification of constancy of	AVCP 4
7. Description of the third party tasks	Not relevant

**8. Declared performance(s):**

Essential characteristics (table ZA.1)	Performance	Harmonised technical specification
Mechanical strength	2,1 N/mm <sup>2</sup>	DS/EN 15435:2008
Thermal resistance	NPD	
Airborne sound insulation	NPD	
Durability	Do not leave exposed	
Water vapour permeability	NPD	
Geometric properties	498 x B x 198 mm. B = [150-190-230-290-330-390] mm	
Maximum deviations (L / B / H)	± 5 / ± 5 / + 3 and -5 mm	
Moisture movement	NPD	
Reaction to fire	Class A1	
Oven dry density	2250 kg/m <sup>3</sup>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Esben Mølgaard, Produktchef

Ikast, 21. May 2013